



VIVA 90/110

Residential Downlights



TRITONE
Colour
Changeable



DIM
Phase Cut
Dimming



IC-4
Covered &
Abutted



YES
Gov
Rebate



35,000hr
Expected
Lifetime



5yr
Warranty

Flush, seamless design.

The VIVA range offers various sized downlights with options of flush or recessed opal diffusers. Tritone colour selection allows easy adjustment of colour temperature. VIVA's flush diffuser with clip-on trims provides a choice of finishes to fit a variety of looks and applications.

Features

- Tritone selectable
- Built-in dimmable driver (1-100%)
- IC-4 rating (ta 25°C)
- Recessed diffuser
- IP44 from below
- Optional clip-on trims in black, brushed nickel and gold








Benefits

- Reduced SKUs and inventory levels
- Ideal for automation control
- Allows for covered or abutted installation
- Minimises glare and enhances visual comfort
- Perfect for wet areas
- Extended application options

POWER	LUMENS	EFFICACY	CCT	CUTOUT	WEIGHT	SAP CODE	PRODUCT CODE
7W	550 lm	79 lm/W	3000K	Ø70mm	0.18kg	2000690	VIVA90-MULTI
	620 lm	89 lm/W	4200K				
	600 lm	86 lm/W	5700K				
9W	840 lm	94 lm/W	3000K	Ø90mm	0.22kg	2000509	VIVA110-MULTI
	880 lm	98 lm/W	4200K				
	850 lm	94 lm/W	5700K				

SPECIFICATIONS	
Body Material:	Polycarbonate
Diffuser Material:	Polycarbonate (Opal)
Fascia Colour:	White: RAL 9003
IP Rating:	Front: IP44 Body: IP20
IC Rating	IC-4 (ta 25°C)
Beam Angle:	50°
CRI:	>80 (>90 option)
SDCM:	<5 (<3 option)
Driver:	Integral
Power Lead:	1.1m Flex & Plug
Input:	220-240V, 50/60Hz
Electrical Classification:	Class 2
Power Factor:	>0.9
Protection:	Overload / Short Circuit
Lifespan:	>50,000hrs @Ta25°C (L70)
Operating Ambient Temperature:	-25 to 50°C
Smart:	KASTA Compatible
Dimming:	Phase-Cut Dimmable (Trailing Edge, 1-100%)

APPLICATIONS
Retail
Hospitality
Function Areas
Office

ACCESSORIES	
Clip-on Trim Black TRB-VIVA90 (SAP 2001058) TRB-VIVA110 (SAP 2000453)	
Clip-on Trim Nickel TRN-VIVA90 (SAP 2000894) TRN-VIVA110 (SAP 2000482)	
Clip-on Trim Gold TRG-VIVA110 (SAP 2000454) (Not available for VIVA90-MULTI)	
Adaptor Ring Ø130mm (Cut Out Ø110-120mm) TRIM-VIVA110-130-W (SAP 2000887) (VIVA110-MULTI only)	
Adaptor Ring Ø170mm (Cut Out Ø110-160mm) TRIM-VIVA110-170-W (SAP 2000663) (VIVA110-MULTI only)	
Surface Mount Kit: SM-ENC-DL (SAP 2001870) (VIVA110-MULTI only)	
Suspension Kit: SM-ENC-SUSKIT (SAP 2001871) (VIVA110-MULTI only)	




VIVA90-MULTI




VIVA110-MULTI

DIMENSIONS



VIVA90-MULTI



VIVA110-MULTI

FIND OUT MORE:

